



Level measurement device with guided radar

- Universal level measurement device for liquids
- Liquid interface measurement
- Insensitive to dust and steam
- 4...20 mA/HART, 2 wires
- ATEX/IECEx certifications

Product variants described in the data sheet may differ from the product presentation and description.

Can be combined with



Type 8619 ▶
multiCELL - Multi-channel and multi-function transmitter/controller



Type 8611 ▶
eCONTROL - Universal controller



Type 8802 ▶
ELEMENT continuous control valve systems - overview



Type 8644 ▶
Remote Process Actuation Control System AirLINE



Type 8793 ▶
Digital electropneumatic Process Controller SideControl

Type description

The Type 8188 is a level measurement device with cable, rod, both interchangeable probe or with coax probe, designed for continuous level measurement.

The unit is suitable for liquids, for industrial use in all areas of process technology. With a measuring range up to 75 m, the 8188 is best suited for tall vessels.

Even process conditions such as strong steam generation, density fluctuations or changes of the dielectric constant do not influence the accuracy of the measurement. Build-up or condensation on the probe or vessel wall do not influence the measuring result.

A liquid interface measurement is also possible with the Type 8188, typically an oil/water interface.

Table of contents

1. General technical data	3
2. Product versions	5
2.1. Rod version.....	5
2.2. Cable version with gravity weight	5
2.3. Coaxial version	6
3. Approvals	7
3.1. Certifications.....	7
4. Materials	7
4.1. Chemical Resistance Chart – Bürkert resistApp.....	7
5. Dimensions	8
5.1. Rod version.....	8
5.2. Cable version with gravity weight	9
5.3. Coaxial version	10
6. Performance specifications	11
6.1. Measuring range and blocking distance diagram.....	11
6.2. Measurement deviation diagram	12
Rod probe version in water.....	12
Rod probe version in oil.....	12
Cable probe version in water	12
Cable probe version in oil	13
Coaxial probe version in water	13
Coaxial probe version in oil.....	13
6.3. Temperature derating diagram.....	14
7. Product operation	14
7.1. Measuring principle	14
7.2. Product operation notes	14
Set up with display/configuration module	14
Set up with PACTware™/DTM and HART communication.....	15
8. Ordering information	15
8.1. Bürkert eShop – Easy ordering and quick delivery.....	15
8.2. Bürkert product filter.....	15
8.3. Ordering chart.....	16
8.4. Ordering chart accessories.....	17

1. General technical data

Product properties

Materials

Please make sure the device materials are compatible with the fluid you are using. Detailed information can be found in chapter [“4.1. Chemical Resistance Chart – Bürkert resistApp” on page 7.](#)

Non wetted parts

Housing	Plastic PBT (Polyester), PPS and stainless steel 316L (1.4404)
Cover	PC transparent
Seal between housing and cover	EPDM
Cable gland	PA
Blind plug	PA
Ground terminal	Stainless steel 316L

Wetted parts

Depending on the device version.

Detailed information can be found in chapter [“2. Product versions” on page 5.](#)

Process seal	NBR with aramid fibres
Dimensions	Detailed information can be found in chapter “5. Dimensions” on page 8.
Weights	Depending on the device version. Detailed information can be found in chapter “2. Product versions” on page 5.
Probe length	Depending on the device version. Detailed information can be found in chapter “2. Product versions” on page 5.
Measured variable	Level of liquids. For solids applications, please contact your local Bürkert Sales Center.
Measuring range	Detailed information can be found in chapter “6.1. Measuring range and blocking distance diagram” on page 11.
Blocking distance	Detailed information can be found in chapter “6.1. Measuring range and blocking distance diagram” on page 11.
Damping (63 % of the input variable)	0...999 s, adjustable
Step response time ^{1.)}	≤ 3 s

Product accessories

Display	LCD in full dot matrix. Detailed information can be found in chapter “8.4. Ordering chart accessories” on page 17
---------	---

Performance data

Measurement deviation ^{2.)3.)}	According to DIN EN 60770-1: ± 2 mm Detailed information can be found in chapter “6.2. Measurement deviation diagram” on page 12.
Measuring range resolution	< 1 mm
Measuring cycle time	< 500 ms
Temperature drift	- Digital output: ± 3 mm/10 K relating to the max. measuring range or max. 10 mm - Current output: < 0.03 %/10K relating to the 16 mA span or ≤ 0.3 %
Max. filling/emptying speed	1 m/min
Non-repeatability	≤ ± 1 mm (max.)
Vibration resistance	Depending on the device version. Detailed information can be found in chapter “2. Product versions” on page 5.
Shock resistance	Depending on the device version. Detailed information can be found in chapter “2. Product versions” on page 5.

Electrical data

Operating voltage (U _n)	- Without display/configuration module: 9.6...35 V DC 9.6...30 V DC (Ex ia instrument) - With display/configuration module: 16...35 V DC 16...30 V DC (Ex ia instrument)
Power source (not supplied)	Limited power source according to UL/EN 60950-1 standards or limited energy circuit according to UL/EN 61010-1 §9.4
Starting current	≤ 3.6 mA, ≤ 10 mA for 5 ms after the switching on
DC reverse polarity protection	Yes

Output signal	4...20 mA/HART
Signal resolution	0.3 μ A
Range of the output signal	3.8...20.5 mA/HART (default setting)
Load resistor	$(U_n - U_{min})/0.022$ A
Fault signal	Current output: last valid measured value, ≥ 21 mA or < 3.6 mA (adjustable)
Max. output current	21.5 mA
Residual ripple (for DC)	- For $9.6 \text{ V} < U_n < 18 \text{ V}$: $\leq 0.7 V_{eff}$ (16...400 Hz) - For $18 \text{ V} < U_n < 35 \text{ V}$: $\leq 1.0 V_{eff}$ (16...400 Hz)
Voltage supply cable	- Cable diameter: 5...9 mm - Wire cross-section (spring-loaded terminals): - Massive wire, stranded wire: 0.2...2.5 mm² (AWG 24...14) - Stranded wire with end sleeve: 0.2...1.5 mm² (AWG 24...16)

Medium data

Process temperature	Depending on the device version. Detailed information can be found in chapter “2. Product versions” on page 5.
Process pressure	Depending on the device version. Detailed information can be found in chapter “2. Product versions” on page 5.
Dielectric constant (min.)	Depending on the device version. Detailed information can be found in chapter “2. Product versions” on page 5.

Product connections

Process connection	Thread G or NPT - $\frac{3}{4}$ ", 1"
Electrical connections	Cable gland M20x 1.5

Approvals and Certificates

Standards

Degree of protection according to IEC/EN 60529	IP66/IP67 with cable plug mounted and tightened M20x 1.5
Overvoltage category according to IEC 61010-1	Category III
Protection class according to IEC 61010-1	Class III

Directives

CE directives	The applied standards, which verify conformity with the EU Directives, can be found on the EU Type Examination Certificate and/or the EU Declaration of conformity (if applicable)
NAMUR recommendations	- NE21 – Electromagnetic compatibility of equipment - NE43 – Signal level for fault information from measuring transducers - NE53 – Compatibility of field devices and display/adjustment components - NE107 – Self-monitoring and diagnosis of field devices

Certifications

IECex / ATEX	IEC/EN60079-0, IEC/EN60079-11, IEC/EN60079-26. Detailed information can be found in chapter “3.1. Certifications” on page 7.
--------------	--

Environment and installation

Ambient temperature	Operation and storage: -40...+80 °C (-40...+176 °F) (with display/configuration module)
Temperature derating	Depending on the device version. Detailed information can be found in chapter “6.3. Temperature derating diagram” on page 14.
Relative air humidity	20...85 %, without condensation
Height above sea level	Max. 2000 m (by default; max. 5000 m with connected overvoltage protection)
Pollution degree	Degree 4 (when used with fulfilled housing protection)


1.) Time span, after a sudden change in the measuring distance of max. 0.5 m in liquid applications, until the output signal has assumed for the first time 90 % of the final value (IEC 61298-2).

2.) Depending on the mounting conditions, deviations can occur which can be rectified by adapting the adjustment or changing the measured value offset in the DTM service mode.

3.) The blocking distances can be optimized by a false signal suppression.


2. Product versions

2.1. Rod version




Product details	
Materials	Wetted parts: - Process connection in: - Stainless steel 316L (1.4404 or 1.4435) and PPS (version up to 6 bar) - Stainless steel 316L (1.4404 or 1.4435) and PEEK (version up to 40 bar) - Process seal on the instrument side (rod lead-through) in EPDM - Rod-Ø 8 mm in stainless steel 316L (1.4404 or 1.4435)
Weights	- Housing: 890 g - Rod-Ø 8 mm: approx. 400 g/m
Probe length	0.3...6 m (lateral load: 10 Nm)
Vibration resistance	- Housing: 4 g with 5...200 Hz according to EN 60068-2-6 (vibration at resonance) - Measuring probe: 1 g with 5...200 Hz according to EN 60068-2-6 (vibration at resonance) with tube length 50 cm
Shock resistance	- Housing: 100 g, 6 ms according to EN 60068-2-27 (mechanical shock) - Measuring probe: 25 g, 6 ms according to EN 60068-2-27 (mechanical shock) with tube length 50 cm
Process temperature	-40...+80 °C (-40...+176 °F) (for version up to 6 bar) -40...+150 °C (-40...+302 °F) (for version up to 40 bar)
Process pressure	-1...+6 bar (-100...+600 kPa/-14.5...+87 psig) (for process connection in stainless steel 316L (1.4404 or 1.4435) and PPS) -1...+40 bar (-100...+4000 kPa/-14.5...+580 psig) (for process connection in stainless steel 316L (1.4404 or 1.4435) and PEEK)
Dielectric constant (min.)	$\epsilon_r > 1.6$

2.2. Cable version with gravity weight



Product details	
Materials	Wetted parts: - Process connection in: - Stainless steel 316L (1.4404 or 1.4435) and PPS (version up to 6 bar) - Stainless steel 316L (1.4404 or 1.4435) and PEEK (version up to 40 bar) - Inner conductor (up to separation cable) in stainless steel 316L (1.4404 or 1.4435) - Process seal on the instrument side (cable lead-through) in EPDM - Cable-Ø 4 mm with gravity weight in stainless steel 316L (1.4404 or 1.4435)
Weights	- Housing: 890 g - Cable-Ø 4 mm: approx. 60 g/m - Gravity weight: approx. 200 g
Probe length	0.5...75 m (max. tensile load: 2.5 kN)
Process temperature	-40...+80 °C (-40...+176 °F) (for version up to 6 bar) -40...+150 °C (-40...+302 °F) (for version up to 40 bar)
Process pressure	-1...+6 bar (-100...+600 kPa/-14.5...+87 psig) (for process connection in stainless steel 316L (1.4404 or 1.4435) and PPS) -1...+40 bar (-100...+4000 kPa/-14.5...+580 psig) (for process connection in stainless steel 316L (1.4404 or 1.4435) and PEEK)
Dielectric constant (min.)	$\epsilon_r > 1.6$

2.3. Coaxial version



Product details	
Materials	Wetted parts: • Process connection in stainless steel 316L (1.4404 or 1.4435) and PEEK • Inner conductor (up to separation cable) in stainless steel 316L (1.4404 or 1.4435) • Process seal on the instrument side (rod lead-through) in EPDM • Coaxial-Ø 21.3 mm (tube) in stainless steel 316L (1.4404 or 1.4435)
Weights	• Housing: 890 g • Coaxial-Ø 21.3 mm: approx. 1110 g/m
Probe length	0.3...6 m (lateral load: 60 Nm)
Dynamic viscosity	0.1...500 mPa s (requirement: with density 1)
Vibration resistance	• Housing: 4 g with 5...200 Hz according to EN 60068-2-6 (vibration at resonance) • Measuring probe: 1 g with 5...200 Hz according to EN 60068-2-6 (vibration at resonance) with tube length 50 cm
Shock resistance	• Housing: 100 g, 6 ms according to EN 60068-2-27 (mechanical shock) • Measuring probe: 25 g, 6 ms according to EN 60068-2-27 (mechanical shock) with tube length 50 cm
Process temperature	-40...+150 °C (-40...+302 °F)
Process pressure	-1...+40 bar (-100...+4000 kPa/-14.5...+580 psig)
Dielectric constant (min.)	$\epsilon_r > 1.4$

3. Approvals

3.1. Certifications


Note:

Devices with Ex or IEC certification have different technical data.

Certificate	Description
	TÜV 14 ATEX 7490 X
	Specifications Ex
	Ex Protection
	Categorie 1G, 1/2G or 2G
	Ex Certification
	EEx ia IIC T6
	Conformity specifications
	Operating voltage Ui
	30 V
	Short circuit rating Ii
	131 mA
	Power limitation Pi
	983 mW
	Ambient temperature
	-50...+46 °C (-58...+114.8 °F) (depending on the categorie)
	Internal capacity Ci
	Negligible
	Internal inductivity Li
	≤5 µH
	IECEX TUR 14.0014 X
	Specifications Ex
	Ex Protection
	Categorie 1G, 1/2G or 2G
	Ex Certification
	EEx ia IIC T6
	Conformity specifications
	Operating voltage Ui
	30 V
	Short circuit rating Ii
	131 mA
	Power limitation Pi
	983 mW
	Ambient temperature
	-50...+46 °C (-58...+114.8 °F) (depending on the categorie)
	Internal capacity Ci
	Negligible
	Internal inductivity Li
	≤5 µH

4. Materials

4.1. Chemical Resistance Chart – Bürkert resistApp



Bürkert resistApp – Chemical Resistance Chart

You want to ensure the reliability and durability of the materials in your individual application case? Verify your combination of media and materials on our website or in our resistApp.


[Start Chemical Resistance Check](#)

5. Dimensions

5.1. Rod version

Note:


Dimensions in mm (unless specified differently)



No.	Element
1	Cable gland M20 × 1.5
2	Blind plug M20 × 1.5
3	AF36 for G or NPT ¾"
4	AF41 for G or NPT 1"
	G or NPT ¾"
	G or NPT ¾"

5.2. Cable version with gravity weight


Note:
Dimensions in mm (unless specified differently)



No.	Element
1	Cable gland M20 × 1.5
2	Blind plug M20 × 1.5
3	AF36 for G or NPT ¾"
4	AF41 for G or NPT 1"
	G or NPT ¾"
	G or NPT ¾"

5.3. Coaxial version


Note:
Dimensions in mm (unless specified differently)



No.	Element
1	Cable gland M20 × 1.5
2	Blind plug M20 × 1.5
3	AF36 for G or NPT ¾"
4	AF41 for G or NPT 1"
	G or NPT ¾"
	G or NPT ¾"

6. Performance specifications

6.1. Measuring range and blocking distance diagram




Range length				
No.	Description	A: rod version	B: cable version	C: coaxial version
1	Reference plane	–	–	–
2	Measuring probe length	0.3...6 m	0.5...75 m	0.3...6 m
3	Measurement range	In water: 0.08...6 m In oil: 0.15...5.95 m	In water: 0.08...75 m In oil: 0.15...74.85 m	In water: 0.03...6 m In oil: 0.10...5.95 m
4	Upper blocking distance	In water: 0.08 m In oil: 0.15 m	In water: 0.08 m In oil: 0.15 m	In water: 0.03 m In oil: 0.10 m
5	Lower blocking distance	In water: 0 m In oil: 0.05 m	In water: 0 m In oil: 0.15 m	In water: 0 m In oil: 0.05 m

6.2. Measurement deviation diagram


Note:

- The blocking distance is indicated by the grey area in the diagram. No measurement is possible in this area.
- The length L represents the length of the probe.


Rod probe version in water



Rod probe version in oil




Cable probe version in water



The drawing shows a mechanical part with a cross-section on the left and a longitudinal section on the right. The cross-section has a total width of 20 mm, with a central hole of diameter 15 mm. The longitudinal section shows a total length of 0,15 m, with a central section of length 0,05 m. The part is made of a material with a yield strength of 200 MPa and a tensile strength of 350 MPa. The part is subjected to a tensile force of 10 kN.

6.3. Temperature derating diagram



7. Product operation

7.1. Measuring principle

High frequency microwave pulses are guided along a steel cable, a rod or a coaxial cable. When they reach the product surface, the microwave pulses are reflected and received by the processing electronics. The running time is evaluated by the instrument and outputted as distance. Time consuming adjustment with medium is not necessary. The instruments are pre-set to the ordered probe length.

The shortenable cable, rod and coaxial versions can be adapted individually to the local requirements.

7.2. Product operation notes

Note:

The measuring device can be adjusted with:


- The display/configuration module
- The suitable Bürkert DTM in conjunction with a software according to the FDT/DTM standard, e.g. PACTware™ and PC
- With a HART handheld

The entered parameters are generally saved in the measuring device Type 8188. Optionally, parameters may also be uploaded and downloaded with the display/configuration module or saved in a file by using PACTware™/8188-DTM.

Set up with display/configuration module

Display/configuration module	Description
	The display/configuration module can be inserted into the measuring device and removed again at any time. It is not necessary to interrupt the power supply. The measuring device is adjusted via the four keys of the display/configuration module.

Set up with PACTware™/DTM and HART communication

Assembly	Description								
	The measuring device can be operated thanks to PACTware™, via HART communication. An interface adapter is necessary for the adjustment with PACTware™. For the setup of the Type 8188, the DTM in the actual version must be used. The basic version of DTM incl. PACTware™ is available as a free-of-charge download from the internet at www.burkert.com ►. Connecting the PC via HART <table border="1"> <thead> <tr> <th>No.</th><th>Description</th></tr> </thead> <tbody> <tr> <td>1</td><td>Measuring device Type 8188</td></tr> <tr> <td>2</td><td>HART-USB Modem</td></tr> <tr> <td>3</td><td>Resistance 250 Ω</td></tr> </tbody> </table> Necessary components: • Measuring device Type 8188 • PC with PACTware™ and suitable Bürkert DTM • HART-USB Modem • Resistance approx. 250 Ω • Power supply unit	No.	Description	1	Measuring device Type 8188	2	HART-USB Modem	3	Resistance 250 Ω
No.	Description								
1	Measuring device Type 8188								
2	HART-USB Modem								
3	Resistance 250 Ω								

8. Ordering information

8.1. Bürkert eShop – Easy ordering and quick delivery

**Bürkert eShop – Easy ordering and fast delivery**

You want to find your desired Bürkert product or spare part quickly and order directly? Our online shop is available for you 24/7. Sign up and enjoy all the benefits.

[Order online now](#)

8.2. Bürkert product filter

**Bürkert product filter – Get quickly to the right product**

You want to select products comfortably based on your technical requirements? Use the Bürkert product filter and find suitable articles for your application quickly and easily.

[Try out our product filter](#)

8.3. Ordering chart

Note:

All following versions are supplied with display/configuration module.

Description	Operating voltage	Output	Probe	Length	Electrical connection	Article no.
Standard version						
G ¾" mounting thread, PN6, temp. max. 80 °C	9.6...35 V DC	4...20 mA/HART (2 wires)	Rod	1 m	Cable gland M20 × 1.5	565800
				2 m		565804
			Cable	5 m		565812
				10 m		565816
			Coaxial	1 m		565823
				2 m		565824
G 1" mounting thread, PN40, temp. max. 150 °C	9.6...35 V DC	4...20 mA/HART (2 wires)	Rod	1 m	Cable gland +M20 × 1.5	565802
				2 m		565806
			Cable	5 m		565814
				10 m		565818
			Coaxial	1 m		565825
				2 m		565826
NPT ¾" mounting thread, PN6, temp. max. 80 °C	9.6...35 V DC	4...20 mA/HART (2 wires)	Rod	1 m	Cable gland M20 × 1.5	565801
				2 m		565805
			Cable	5 m		565813
				10 m		565817
			Coaxial	1 m		565827
				2 m		565828
NPT 1" mounting thread, PN40, temp. max. 150 °C	9.6...35 V DC	4...20 mA/HART (2 wires)	Rod	1 m	Cable gland M20 × 1.5	565803
				2 m		565807
			Cable	5 m		565815
				10 m		565819
			Coaxial	1 m		565829
				2 m		565830
Ex version - ATEX certification						
G ¾" mounting thread, PN6, temp. max. 80 °C	9.6...30 V DC	4...20 mA/HART (2 wires)	Rod	1 m	Cable gland M20 × 1.5	565808
				2 m		565810
			Cable	5 m		565820
				10 m		565831
			Coaxial	1 m		565832
				2 m		565832
G 1" mounting thread, PN40, temp. max. 150 °C	9.6...30 V DC	4...20 mA/HART (2 wires)	Rod	1 m	Cable gland M20 × 1.5	565809
				2 m		565811
			Cable	5 m		565821
				10 m		565833
			Coaxial	1 m		565833
				2 m		565834
Ex version - IECEx certification						
NPT ¾" mounting thread, PN6, temp. max. 80 °C	9.6...30 V DC	4...20 mA/HART (2 wires)	Rod	1 m	Cable gland M20 × 1.5	565839
				2 m		565840
			Cable	5 m		565841
				10 m		565835
			Coaxial	1 m		565836
				2 m		565836
NPT 1" mounting thread, PN40, temp. max. 150 °C	9.6...30 V DC	4...20 mA/HART (2 wires)	Rod	1 m	Cable gland M20 × 1.5	565842
				2 m		565843
			Cable	5 m		565844
				10 m		565837
			Coaxial	1 m		565837
				2 m		565838

Further versions on request			
	Material - FFKM - Alloy C22 (2.4602)		Temperature -40...+200 °C
	Process connection - Thread G or NPT ½" (PN40 ,150 °C), 1½" - Flange DN25, DN40, DN50, DN80, DN100, DN150 - Flange 1", 1 ½", 2", 3", 4", 6"		Additional With display

8.4. Ordering chart accessories

Description	Article no.
Set with 2 reductions M20 × 1.5/NPT ½" + 2 neoprene flat seals for cable gland + 2 screw-plugs M20 × 1.5	551782 
Hart-USB Modem	560177 
Set with a display/configuration module, a transparent cover and a seal ring	559279 
Set with a transparent cover and a seal ring	561006 

Bürkert – Close to You

For up-to-date addresses
please visit us at
www.burkert.com

DTS 1000244851 EN Version: | Status: RL (released | freigegeben | valide) printed: 27.11.2020

Austria
Belgium
Czech Republic
Denmark
Finland
France
Germany
Italy
Netherlands

Norway
Poland
Spain
Sweden
Switzerland
Turkey
United Kingdom

Russia

Canada
USA

Brazil
Uruguay

South Africa

United
Arab
Emirates

Australia
New Zealand

China
Hong Kong
India
Japan
Korea
Malaysia
Philippines
Singapore
Taiwan